

BLACK

NITRILE

NON-STERILE

AMBIDEXTROUS

BEADED CUFF

NON-LATEX

TEXTURED FINGERS

FOR SINGLE USE ONLY

POWDER-FREE EXAMINATION GLOVES

The deep black color makes this glove ideal when working around dirt, grime and oils. Nitrile construction with textured fingers provides comfort with a great grip.

- Deep black color provides framing effect
- Popular across a wide array of industries
- Finger textured for firm and consistent grip



IDEAL FOR WORK AREAS WHERE THE JOB GETS MESSY

PRODUCT CODE		PACKA	PACKAGING	
S	N641	100	Gloves/Box	
М	N642	10	Boxes/Case	
L	N643			
XL	N644			
XXL	N645			

GLOVE PROFILE		ASTM D 6319	ONYX®
Length	mm (inches)	min. 220 (8.7)	245 (9.6)
Cuff Thickness	mm (mils)	n/a	0.07 (2.8)
Palm Thickness	mm (mils)	min. 0.05 (2.0)	0.09 (3.5)
Finger Thickness	mm (mils)	min. 0.05 (2.0)	0.13 (5.1)
Tensile Strength	Before Aging After Aging	min. 14 min. 14	42 min. 14
Elasticity/Elongation	Before Aging After Aging	min. 500 min. 400	500 400
Pinhole Defect Rate*	(AQL)	max. 2.5	1.5

* Pinhole Defect Rate is FDA minimum requirement.



RECOMMENDED INDUSTRIES

Image is a state of the second of the se

